



Creativity Progress & Excellence

Network Product





# IPR712S

## Day & Night 720P HD IR IP Camera



### Features


- HD megapixel CMOS image sensor
- True H.264 AVC/MPEG-4 part 10 real-time video compression
- H.264 and Motion JPEG multi-profile video streaming
- High efficiency IR LED, radiant distance up to 16m
- Day and night function with mechanical IR cut filter
- Aluminum housing with IP66 rating
- Perfect solution for day/night applications
- Onvif supported



### Dimensions

Body: 82mm(W) x 72.5mm(H) x 154mm(D)

Bracket: 101mm(L)  
(Unit:mm)



IP CAMERA SERIES		
Day & Night 720P HD IR IP Camera		
Model	IPR712S4.3	IPR712S6
Lens	Focal Length	4.3mm / 6mm
	Iris	F1.8
	Angle of View	49.8°(H) , 36.8°(V) , 63.6°(D) / 35.8°(H) , 26.5°(V) , 45.7°(D)
Pick Up Element	1/4" Progressive scan CMOS sensor	
Effective Pixel	1280(H) x 800(V) = 1,024,000(pixel)	
Chip Size	3.88mm(H) x 2.43mm(V)	
Scanning System	Progressive Scan	
Infrared Cut Filter	Auto / Schedule / Day (Color) / Night (Mono)	
Min. Illumination	Color : 3 Lux at F1.8, Mono : 0.6 Lux at F1.8 / 0 Lux with IR	
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2	
Sense Up	Off / 1 Frame / 2 Frames / 3 Frames / 7 Frames	
Back Light Compensation	Auto	
Electronic Shutter	1/30(25)s ~ 1/20,000s	
IP Rating	IP66	
Window	Ø65 Heat Resistant Glass	
Infrared LED	Peak Wavelength	850nm
	Beam Spread	30°
	Radiant Distance	16M
Operating Temperature	-35°C ~ +50°C (-31°F ~ 122°F)	
Dimension	Body : 82mm(W) x 72.5mm(H) x 154mm(D) / Bracket : 101mm(L)	
Weight	600g	
Power Input Voltage	DC12V ±10%	
Power Consumption	10W	
Peripheral Products	IJ1748D 17W (PoE Injector) SL1212D 12W (PoE Splitter)	

NETWORK	
Video Compression	H.264/AVC, Motion JPEG
Resolution	720P(1280 x 768) / VGA(640 x 384) / CIF(320 x 192)
Multiple profile	Stream 4 profiles : H.264 at 720P, JPEG at 720P, H.264 at VGA, JPEG at CIF
Frame Rate	H.264 : up to 20 fps at 720P, MJPEG : up to 10 fps at 720P
Video Streaming	RTSP : RTP/HTTP, RTP/TCP, RTP/UDP
Video Bitrate	128Kbps ~ 5Mbps
Security	Base64 HTTP encryption
	Multiple user access levels with password protection
	10 user accounts available
Users	8 simultaneous users
Digital Zoom	Yes
Motion Detection	Events triggered by built-in motion detection
	Motion triggering recording into SD card Image upload over FTP, e-mail by motion detection
CPU, Memory	Embedded SoC ARM9, 500MHz, 64MB DDR, 8MB flash memory
Maintenance	Firmware update via HTTP, Firmware available at web site
Network Interface	10Mbps / 100Mbps Base-T, RJ-45
PC requirement	OS : Windows 2000, Windows XP, Windows Vista, Windows 7
	Browser : Windows Internet Explore 6, 7, 8
	CPU : Intel Pentium 4 1.8GHz or above RAM : 1GB or above, Independent Display Card
Network Protocols	IP, TCP, UDP, HTTP, SMTP, ESMTMP, NTP, DDNS, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet
Mobile Phone and PDA	iPhone, iPad, and Android support
System Integration	Onvif
CMX	Support CMX HD 3.2 / 3.6
Video Display	LILIN Universal ActiveX
OS	Embedded Linux 2.4.19
SD Card recording	Support SD/SDHC card for circular recording (card is not included)