

# Volume Extraction

## WFE 2ES / WFE 2CS

Fume extraction unit  
as economical solution



Portable fume extraction kit for one work station

The fume extraction unit WFE 2ES is easy to install and operate. It is designed as a smaller central system and is supplied complete with flexible hose, arm and bracket, ready for installation at the workplace.



Technical Data	
Maximum capacity	2 work places
Maximum extraction rate	220 m³/h
Sound level	55 db (A) at 1 m distance
Operating voltage	230V / 50Hz (115V / 60Hz)
Power input	115 VA
Maximum vacuum	1.800 Pa
Dimensions (L x W x H)	320 x 320 x 395 mm 12.6 x 12.6 x 15.5 in
Weight	9 kg / 19.8 lb

### Scope of supply

- 005 36 506 99 WFE 2ES Fume extraction unit consists of:  
HEPA filter H12, active carbonate foam
- Fine dust pre-filter F5
- 005 36 571 99 KIT 1 WF Funnel 60 consists of:  
005 36 578 99 Extraction arm  
005 36 573 99 Funnel nozzle  
005 36 574 99 Stop valve  
005 36 575 99 Bench mounting clamps, 2 x  
005 36 576 99 Extraction hose, 3 m

Order No. 230V	005 36 516 89
Order No. 120V	WFE2ES KIT1

### Option: Arm with sloped nozzle

- 005 36 572 99 KIT 1 WF Sloped 60 for volume extraction consists of:  
005 36 578 99 Extraction arm  
005 36 577 99 Sloped nozzle  
005 36 574 99 Stop valve  
005 36 575 99 Bench mounting clamps, 2 x  
005 36 576 99 Extraction hose, 3 m

### Option: WFE 2CS with speed control

Order No. 230V	005 36 526 99
Order No. 120V	WFE2CS

### Attributes

- Mobile fume extraction unit purifies air up to 2 workplaces
- Easy filter exchange
- Quick and simple installation
- Optional: Speed control (WFE 2CS)



ESD safe



low sound level

